



NOTES:

1. Rating: UL 25 A  
IEC 24 A  
PITCH: 5.10mm
2. Insulation Resistance:  
500M $\Omega$  or more at DC500V
3. Using Temperature Range:  
-40°C~+105°C
4. RoHS Compliance

P	2	3	4	5	6
U	5.10	10.20	15.30	20.40	25.50
V	9.70	14.80	19.90	25.00	30.10
P	7	8	9	10	
U	30.60	35.70	40.80	45.90	
V	35.20	40.30	45.40	50.50	

Normal Geometric Tolerancing					
—	//	≡	⊥		
0 to 100	0.2		0 to 10	0.2	
over 100 to 150	0.3	0.3	over 10	0.3	
over 150	0.5				
Total Pitch Tolerances			Normal dimension Tolerances		
0<U<=30	±0.20		0~30	±0.25	
30<U<=53	±0.25		over 30~53	±0.30	
53<U<=70	±0.30		over 53~70	±0.35	
70<U<=90	±0.35		over 70~90	±0.44	
90<U<=115	±0.44		over 90~115	±0.55	

包射的金属材料		COPPER ALLOY		Tin Plated	
1	MOLDING PLASTIC	PA66		UL94-V0	GREY
ITEM	NAME OF PART		MATERIAL		NOTES

DWG.	W K	DATE	11.06.23	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	5:1 ( : )		
APP.		DATE					
				NAME	CSC-2.5XXPS		
				DWG NO.	SP-03-CSC25XXS		

2			
REV.	CONTENT	CHK.	DATE