



NOTES:

- Rating: UL 35 A
IEC 32 A
PITCH: 6.10mm
- Insulation Resistance:
500MΩ or more at DC500V
- Using Temperature Range:
-40°C~+105°C
- RoHS Compliance

P	2	3	4	5	6
U	6.10	12.20	18.30	24.40	30.50
V	11.60	17.70	23.80	29.90	36.00
P	7	8	9	10	
U	36.60	42.70	48.80	54.90	
V	42.10	48.20	54.30	60.40	

Normal Geometric Tolerancing			
—	//	≡	⊥
0 to 100	0.2	0 to 10	0.2
over 100 to 150	0.3	over 10	0.3
over 150	0.5		
Total Pitch Tolerances		Normal dimension Tolerances	
0<U<=30	±0.20	0~30	±0.25
30<U<=53	±0.25	over 30~53	±0.30
53<U<=70	±0.30	over 53~70	±0.35
70<U<=90	±0.35	over 70~90	±0.44
90<U<=115	±0.44	over 90~115	±0.55

包射的金属材料		COPPER ALLOY	Tin Plated
1	MOLDING PLASTIC	PA66	UL94-V0 GREY
ITEM	NAME OF PART	MATERIAL	NOTES

DWG.	W K	DATE	11.06.23	UNITS	MM	SHEET/OF	1 / 1
CHK.		DATE		SCALE	5:1 (:)		
APP.		DATE					
				NAME	CSC-4XXPS		
				DWG NO.	SP-03-CSC4XXPS		

REV.	CONTENT	CHK.	DATE
------	---------	------	------



DINKLE
ENTERPRISE CO., LTD