





POS.	P/N.	A	B	C	D
04	TM0520-0004	1.5	5.5	2.8	6.1
06	TM0520-0006	2.5	6.5	3.8	7.1
08	TM0520-0008	3.5	7.5	4.8	8.1
10	TM0520-0010	4.5	8.5	5.8	9.1
12	TM0520-0012	5.5	9.5	6.8	10.1
14	TM0520-0014	6.5	10.5	7.8	11.1
15	TM0520-0015	7.0	11.0	8.3	11.6
16	TM0520-0016	7.5	11.5	8.8	12.1
18	TM0520-0018	8.5	12.5	9.8	13.1
20	TM0520-0020	9.5	13.5	10.8	14.1
22	TM0520-0022	10.5	14.5	11.8	15.1
24	TM0520-0024	11.5	15.5	12.8	16.1
26	TM0520-0026	12.5	16.5	13.8	17.1
28	TM0520-0026	13.5	17.5	14.8	18.1
30	TM0520-0030	14.5	18.5	15.8	19.1
40	TM0520-0040	19.5	23.5	20.8	24.1
45	TM0520-0045	22.0	26.0	23.3	26.6
50	TM0520-0050	24.5	28.5	25.8	29.1
54	TM0520-0054	26.5	30.5	27.8	31.1
60	TM0520-0060	29.5	33.5	30.8	34.1



PCB PATTERN LAYOUT



T=0.3 ±0.05
(Conductive plating)

How To Order

TM0520-00XX

- NO of Contact Position (04pin~60pin)
- Standaed Type
- Height (2.0mm)
- 0.5mm FPC Conmector Siereies

I/NO	DESCRIPTION	MATERIAL	FINISHED	Q'TY(unit:pcs)	REMARK
4	LATCH	PHOS. BRZ	Sn(2~5)UM	2	
3	TERMINALS	PHOS. BRZ	CONTACT:AU	NN	
2	HANDLE	PPS	UL 94V-0	1	
1	HOUSING	PA 6T	UL 94V-0	1	

LTR	REVISION RECORD	ECR	ECN	DRG	CHK	DATE
A	FIRST RELEASE			LMH	YHS	2005-03-14

DO NOT SCALE DRAWING

FORM NO.: TM-FS-END-030-A

APPROVED	BY:T.N.K.
CHECKED	BY:Y.H.S.
DRAWING	BY:L.M.H

GENERAL TOLERANCES

X:	±0.25
.X:	±0.15
.XX:	±0.10
X:	±2.0°
X.X:	±1.0°
X.XX:	±0.5°

SHEET 1 OF 1

TM TECH CO.,LTD.

TITLE:	TM0520
PART NO:	TM0520-00XX
DWG NO:	E-TM0520-00XXA
UNIT:MM	SCALE : 1:1 REV: A

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO TM TECH CO.,LTD.AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.